

Unique Features, Universal Connectivity

Serial Drivers

- Allen-Bradley DF1 Half and Full Duplex (PLC-5, SLC 500, MicroLogix 1000, 1200 and 1500)
- DH485/AIC/AIC+ for MicroLogix 1000, 1200, 1500, SLC500, 5/01, /02, /03
- Aromat Mewtocol COM
- Baldor
- Control Techniques - Unidrive 2-wire, 4-wire (binary)
- Control Technology Corp. (CTC) - CTC2600, 2700 and 5100 (CTC Binary)
- GE Fanuc SNPX (90/30, 90/70)
- Idec Computer Link
- All Mitsubishi FX Series
- Modicon MODBUS RTU
- Omron Host Link (C200 and C500)
- Parker Hannifan
- Siemens S7 MPI Adapter series PLCs
- Siemens S7-200
- Square D Symax - 300 Series CPU, 400 Series CPU (Symax)
- Texas Instruments - TI5x5 Series, TI505, TI545-1102, TI545-1104 (Transparent Byte Protocol or Non-Intelligent Terminal Protocol)
- Uni-Telway - Telemecanique TSX 37 Micro (UNI-TE Version 1.1)
- Yaskawa (Memobus protocol)



Simultaneous Communication

Dual Drivers

Toughpanels have the **ability** to communicate to two PLCs **simultaneously**. For example **you** can connect to **profibus on the network** side and DH485 or DF1 on the PLC side. Only **one network** card is allowed in a Toughpanel.